

```
<?xml version="1.0" encoding="iso-8859-1"?>
<beans default-autowire="no">
    <!-- create a proxy to point to the actual target -->
    <bean id="Test" class="coldspring.aop.framework.ProxyFactoryBean">
<property name="target"><ref bean="Test1" /></property>
    <property name="interceptorNames">
        <list>
            <value>sample</value>
        </list>
    </property>
</bean>
<bean id="TestConfig" class="Test.common.config.ValidationConfig"
singleton="true">
<constructor-arg name="delimiter">
<!-- the value given here is a single literal tab, which actually works as the
argument value -->
<value>    </value>
</constructor-arg>
<constructor-arg name="rules">
<map>
<entry key="notempty">
<map>
<entry key="minoccurs">
<value>1</value>
</entry>
<entry key="maxoccurs">
<value>*</value>
</entry>
<entry key="regex">
<value><![CDATA[\w]]></value>
```

```
</entry>
<entry key="message">
<value>You can't validate an empty config.</value>
</entry>
</map>
</entry>
<entry key="illegalchars">
<map>
<entry key="minoccurs">
<value>0</value>
</entry>
<entry key="maxoccurs">
<value>0</value>
</entry>
<entry key="regex">
<value><![CDATA[[^\a-zA-Z_0-9-'\+\~\.\@]]></value>
</entry>
<entry key="message">
<value><![CDATA[Valid characters are: letters (A-Z, either case), numbers (1-9),
hyphen (-), underscore (_), tilde (~), plus (+), backslash (\) and apostrophe
(').]]></value>
</entry>
</map>
</entry>
</map>
</constructor-arg>
</bean>
<bean id="TextEditor" class="test.common.Testeditor.editor" singleton="true"
autowire="no">
<property name="Toolbar"><value>Default</value></property>
```

```
<property name="InstanceName"><value>TextEditor</value></property>
<property name="Content"><value></value></property>
<property name="BasePath"><value>/Testeditor</value></property>
<property name="Width"><value>90%</value></property>
<property name="Height"><value>200</value></property>
<property name="Config"><map><entry
key="foo"><value></value></entry></map></property>
</bean>
</beans>L
```